

# F104-LED SERIES

## SPECIFICATIONS



**Housing**

Made from heavy duty cast aluminum to withstand harsh weather.

**Hardware**

All exposed hardware is made of durable stainless steel, with industrial strength seals.

**Interior Design & Optical**

Energy efficient LED driver is mounted on a removable plate, with quick disconnect wiring to allow easy driver maintenance.

L70 at 50,000 hours with CRI≥70.

**Exterior Design & Finish**


Luminaire is designed to fit post top mounting or pendant mounting with our ornamental arms and poles, and is suitable for wet locations.

Finish is electrostatically applied with thermoset polyester powder-coat.

## SIZES


	length	width	height	weight	tenon size	EPA
Large	20"	20"	42"	26 lbs	3"(W) x 4"(L)	1.85 ft <sup>2</sup>
Small	16"	16"	37"	24 lbs	3"(W) x 4"(L)	0.75 ft <sup>2</sup>

## PHOTOMETRICS



← polar graph

SAMPLE ILLUSTRATION  
IES type III, short



ISO footcandle →

PRODUCT	FITTER	DIFFUSER TYPE	WATTAGE		CCT	VOLTAGE	OPTICS	OPTIONS	FINIALS	COLOR
F104-L	A	CAC CLEAR ACRYLIC	LED	CORN LAMP	3000K	120V~277V	IES TYPE	DIM	N/A	STANDARD RAL
F104-S	B		35W	27W	4000K		II (2)	DIMMING CONTROL		6005 GREEN
	C	CPC CLEAR POLYCARBONATE	50W	36W	5000K	STEP DOWN	III (3)			7012 GREY
	D		55W	45W	6000K	TRANSFORMER	IV (4)	FUS		8019 BRONZE
	E	EAC EXTERNAL PRISMATIC	70W	54W		347V	V (5)	INTERNAL FUSING		9011 BLACK
	F	ACYLIC	90W	80W	± 10%	480V				9016 WHITE
	G		120W		VARIANCE			PCB		*TEXTURE AVAILABLE
	H	EPC EXTERNAL PRISMATIC						BUTTON TYPE PHOTOCCELL		
	I	POLYCARBONATE	CUSTOM							CUSTOM RAL
	J							HSS		
	K	FAC FROSTED ACRYLIC						HOUSE SIDE SHIELD		
L										
Q	FPC FROSTED POLYCARBONATE						TWL			
R							TWIST LOCK SYSTEM			
T	WAC WHITE ACRYLIC									
U	WPC WHITE POLYCARBONATE						WIRELESS CONTROL AVAILABLE			

Product ordering sample F104 - L - A - FAC - 35LED - 3000K - 120~277V - TYPE II - DIM - FA - RAL9011 BLACK