



(C) 2001 HCI (Heritage Casting & Ironworks). Illustrations are copyrighted. Unauthorized reproduction prohibited. In an ongoing effort to improve quality/design, Heritage reserves the right to modify specifications without notice.

**Diffuser Holder Material:** Cast aluminum. Diffuser is attached with 4 stainless steel screws.

**Diffuser Material:** Lower section is U.V. stabilized acrylic and upper section is U.V. stabilized textured polycarbonate.

**Hardware:** Stainless steel.

**Ballast:** HPS high power factor mounted on removable plate. A quick disconnect wiring system allows for fast easy ballast maintenance.

Wattage - 150W (CWI)  
Voltage - 120/240V (240V wired)  
Socket - Mogul (4KV).  
(with cover)  
WIRING DIAGRAM  
CSA STICKER ONLY

**Optical System:** External prismatic refractor with a internal downlight reflector.

**Light Distribution:** IES Type II

**Photocontrol:** Provision only.

**Tenon info:** 3 1/2"H x 3 1/2"OD

**Finish:** Electrostatically applied thermoset polyester powder-coat with the XL4 four part corrosion inhibiting process.

**Colour:** Semi Gloss BLACK  
RAL # 9011

## Approval Drawing

Luminaire: F107-L-K35

Date: Aug 8, 2001 Drawing No: 2952C  
Model: F107-L-K35-150HPS-240V-  
-TYPEII-PCB1L

Project: City of Calgary

Approved as illustrated: ☐ Date:

Approved with changes: ☐ Date:

Approved By:

Type: Notes:

Please Note: Fabrication will not begin until this drawing is approved, signed and returned to HCI



1280 Fewster Drive, Mississauga, Ontario, Canada L4W 1A4  
Tel: (905) 238-2648 Fax: (905) 238-9060  
Toll Free Canada & USA 1-800-267-3175  
E: sales@hclighting.com WEB: www.hclighting.com