

F146-LED SERIES

SPECIFICATIONS



Housing

Made from heavy duty cast aluminum to withstand harsh weather.

Hardware

All exposed hardware is made of durable stainless steel, with industrial strength seals.

Interior Design & Optical

Energy efficient LED driver is mounted on a removable plate, with quick disconnect wiring to allow easy driver maintenance.

L70 at 50,000 hours with CRI≥70.

Exterior Design & Finish


Luminaire is designed to fit post top mounting or pendant mounting with our ornamental arms and poles, and is suitable for wet locations.

Finish is electrostatically applied with thermoset polyester powder-coat.

SIZES


	length	width	height	weight	tenon size	EPA
Large	23"	23"	38"	50 lbs	3"(W) x 4"(L)	3.00 ft ²
Small	-	-	-	-	-	-

PHOTOMETRICS



← polar graph

SAMPLE ILLUSTRATION
IES type V, short



ISO footcandle →

PRODUCT	FITTER	DIFFUSER TYPE	WATTAGE	CCT	VOLTAGE	OPTICS	OPTIONS	FINIALS	COLOR
F146-L	N/A	CAC CLEAR ACRYLIC	LED	3000K	120V~277V	IES TYPE	CHY DECORATIVE	N/A	STANDARD RAL 6005 GREEN 7012 GREY 8019 BRONZE 9011 BLACK 9016 WHITE <i>*TEXTURE AVAILABLE</i> CUSTOM RAL
		CPC CLEAR POLYCARBONATE	35W	4000K	II (2)	CHIMNEY			
		CFA CLEAR & FROSTED ACRYLIC	50W	5000K	III (3)	DIM DIMMING CONTROL			
		CFP CLEAR & FROSTED POLYCARBONATE	55W	6000K	IV (4)	FUS INTERNAL FUSING			
		CTG CLEAR TEMPERED GLASS	70W	± 10% VARIANCE	V (5)	PCB BUTTON TYPE			
		WAC WHITE ACRYLIC	80W	480V	PHOTOCELL				
		WPC WHITE POLYCARBONATE	90W		PEC TWIST LOCK				
			120W		PHOTOCELL				
	CUSTOM		HSS HOUSE SIDE SHIELD						

Product ordering sample

F146 - L - CAC - LED35W - 3000K - 120~277V - TYPE II - CHY - RAL9011 BLACK