

F148-LED SERIES

SPECIFICATIONS



Housing

Made from heavy duty cast aluminum to withstand harsh weather.

Hardware

All exposed hardware is made of durable stainless steel, with industrial strength seals.

Interior Design & Optical

Energy efficient LED driver is mounted on a removable plate, with quick disconnect wiring to allow easy driver maintenance.
L70 at 50,000 hours with CRI≥70.


Exterior Design & Finish

Luminaire is designed to fit post top mounting or pendant mounting with our ornamental arms and poles, and is suitable for wet locations.
Finish is electrostatically applied with thermoset polyester powder-coat.

SIZES


	length	width	height	weight	tenon size	EPA
Large	25"	25"	22"	35 lbs	3"(W) x 4"(L)	1.70 ft ²
Small	-	-	-	-	-	-

PHOTOMETRICS



← polar graph

SAMPLE ILLUSTRATION
IES type V, short



ISO footcandle →

PRODUCT	FITTER	DIFFUSER TYPE	WATTAGE	CCT	VOLTAGE	OPTICS	OPTIONS	FINIALS	COLOR	
F148-L	N/A	CAC CLEAR ACRYLIC	LED	3000K	120V~277V	IES TYPE II (2)	CHY DECORATIVE CHIMNEY	N/A	STANDARD RAL 6005 GREEN 7012 GREY 8019 BRONZE 9011 BLACK 9016 WHITE *TEXTURE AVAILABLE CUSTOM RAL	
			35W	4000K						STEP DOWN TRANSFORMER
			50W	5000K						
		CPC CLEAR POLYCARBONATE	55W	6000K	480V	V (5)	DIM DIMMING CONTROL			
			70W	± 10% VARIANCE						
			80W							
		SAC STIPLE ACRYLIC	90W	CUSTOM			FUS INTERNAL FUSING			
			120W							
		SPC STIPPLE POLYCARBONATE					PCB BUTTON TYPE PHOTOCCELL			
										HSS HOUSE SIDE SHIELD

Product ordering sample

F148 - L - CAC - LED35W - 3000K - 120~277V - TYPE II - CHY - RAL9011 BLACK