

PRODUCT TECHNICAL DATA SHEET

F150-LED SERIES

SPECIFICATIONS

**Housing**

Made from heavy duty cast aluminum to withstand harsh weather.

Hardware

All exposed hardware is made of durable stainless steel, with industrial strength seals.

Interior Design & Optical

Energy efficient LED driver is mounted on a removable plate, with quick disconnect wiring to allow easy driver maintenance.

L70 at 50,000 hours with CRI≥70.

Exterior Design & Finish


Luminaire is designed to fit post top mounting or pendant mounting with our ornamental arms and poles, and is suitable for wet locations.

Finish is electrostatically applied with thermoset polyester powder-coat.

SIZES

	length	width	height	weight	tenon size	EPA
Medium	16"	16"	39"	45 lbs	3"(W) x 4"(L)	2.45 ft ²
Small	14"	14"	29"	28 lbs	3"(W) x 4"(L)	1.90 ft ²


PHOTOMETRICS



SAMPLE ILLUSTRATION
IES type III, short

← polar graph

ISO footcandle →



PRODUCT	FITTER	DIFFUSER TYPE	WATTAGE	CCT	VOLTAGE	OPTICS	OPTIONS	FINIALS	COLOR
F150-M	N/A	CAC CLEAR ACRYLIC	LED	3000K	120V~277V	IES TYPE	CHY DECORATIVE	N/A	STANDARD RAL
F150-S		CPC CLEAR POLYCARBONATE	35W	4000K		II (2)	CHIMNEY		6005 GREEN
		CTG CLEAR TEMPERED GLASS	50W	5000K	STEP DOWN	III (3)			7012 GREY
		FAC FROSTED ACRYLIC	55W	6000K	TRANSFORMER	IV (4)	DIM DIMMING CONTROL		8019 BRONZE
		FPC FROSTED POLYCARBONATE	70W		347V	V (5)	FUS INTERNAL FUSING		9011 BLACK
		WAC WHITE ACRYLIC	80W	± 10% VARIANCE	480V		PCB BUTTON TYPE		9016 WHITE
		WPC WHITE POLYCARBONATE	90W				PHOTOCELL		*TEXTURE AVAILABLE
			120W						CUSTOM RAL
			CUSTOM				PEC TWIST LOCK		
							PHOTOCELL		
							HSS HOUSE SIDE SHIELD		
							TWL TWIST LOCK SYSTEM		

Product ordering sample

F150 - M - CAC - LED35W - 3000K - 120~277V - TYPE II - CHY - RAL9011 BLACK