

Diffuser Type: Clear **Diffuser Material:** Acrylic U.V. stabilized.

Hardware: Stainless steel.

Luminaire Housing: Spun and cast aluminum combination. Top is fully hinged for easy acces to lamp and ballast. (Lamp by others)

Ballast: MH high power factor mounted on removable plate. A quick disconnect wiring system allows for fast easy ballast maintenance.

Wattage - 100W Voltage - 120V

Socket - Medium (4KV).

Photocontrol: Luminaire integrated "twist-lock" type photocell 120V.

Optical System:Roadway type multi faceted, highly polished cutoff reflector.

Light Distribution: IES Type III

Arm: Decorative cast aluminum. PLEASE SPECIFY MOUNTING OPTION

Finish: Electrostatically applied thermoset polyester powder-coat withthe XL4 four part corrosion inhibiting process.

Colour: Green RAL # 6005

Approval Drawing

Luminaire: F162-L- A333WS

Date: July 10, 2003 Drawing No: 4366 Model: F162-L-J3-CAC-100MH-120V-SR-3-PHC-

-A333-WS-RAL6005 Project: Old Cabbagetown BIA

Please Note: Fabrication will not begin until this drawing is approved, signed and returned to HCl



1280 Fewster Drive, Mississauga, Ontario, Canada L4W 1A4
Tel: (905) 238-2648 Fax: (905) 238-9060
Toll Free Canada & USA
E: sales@hcilighting.com Fax: (905) 238-9060
WEB: www.hcilighting.com