
PRODUCT TECHNICAL DATA SHEET

HCI LIGHTING
HERITAGE CASTING & IRONWORKS LTD.

F172-LED PENDANT SERIES

SPECIFICATIONS



Housing
Made from heavy duty cast aluminum to withstand harsh weather.

Hardware
All exposed hardware is made of durable stainless steel, with industrial strength seals.


Interior Design & Optical
Energy efficient LED driver is mounted on a removable plate, with quick disconnect wiring to allow easy driver maintenance.
L70 at 50,000 hours with CRI≥70.

Exterior Design & Finish
Luminaire is designed to fit post top mounting or pendant mounting with our ornamental arms and poles, and is suitable for wet locations.
Finish is electrostatically applied with thermoset polyester powder-coat.

SIZES

	length	width	height	weight	tenon size	EPA
Large	24”	24”	28”	33 lbs	3”(W) x 4”(L)	1.15 ft²
Small	18”	18”	20”	22 lbs	3”(W) x 4”(L)	0.85 ft²


PHOTOMETRICS



polar graph

SAMPLE ILLUSTRATION
IES type III, short

ISO footcandle



PRODUCT	FITTER	DIFFUSER TYPE	WATTAGE	CCT	VOLTAGE	OPTICS	OPTIONS	FINIALS	COLOR
F172-L F172-S	N/A	CPC CLEAR POLYCARBONATE	LED 35W 50W 55W 70W 80W 90W 120W CUSTOM	3000K 4000K 5000K 6000K ± 10% VARIANCE	120V~277V STEP DOWN TRANSFORMER 347V 480V	IES TYPE II (2) III (3) V (5)	DIM DIMMING CONTROL FUS INTERNAL FUSING PCB BUTTON TYPE PHOTOCELL HSS HOUSE SIDE SHIELD TWL TWIST LOCK SYSTEM	N/A	STANDARD RAL 6005 GREEN 7012 GREY 8019 BRONZE 9011 BLACK 9016 WHITE *TEXTURE AVAILABLE* CUSTOM RAL

Product ordering sample F172 - L - CPC - LED35W - 3000K - 120~277V - TYPE II - DIM - RAL9011 BLACK

© 2015 HCI LIGHTING. We reserve the rights to change the product and its information without notice.