


F187 SERIES LUMINAIRE



HCI
Heritage Casting & Ironworks

1280 Fewster Drive
Mississauga ON L4W 1A4
sales@hclighting.com
www.hclighting.com
Fax (905) 238-9060

Toll-free (800) 267-3175 Tel. (905) 238-2648



F187-L
Weight: 25 lbs
EPA: 2.4 sq ft

Description. The F187 Series luminaire shall consist of a prismatic diffuser, an internal multi-faceted reflector and a spun aluminum body with a cast aluminum top cap. The top cap shall be equipped with an access door for easy ballast service. The hinged diffuser shall be secured to the gasketed luminaire body with a security clamp. The ballast shall feature quick disconnect plugs for easy ballast maintenance. The ballast shall be factory wired, tested and mounted on a removable cast aluminum plate together with a 4kV porcelain socket. Lamps are not included and shall be supplied by others. All electrical components shall be UL listed and labeled.

Installation. The fixture shall be equipped with either a 2" OD or 3-1/2" OD tenon and shall be secured to an arm with three hex socket screws spaced 120° apart and a security bolt.

Finish. All applicable parts shall receive a standard electrostatically applied thermoset polyester powder coat smooth semi gloss finish with a four part corrosion inhibiting process.

To assemble a catalog number, list all codes sequentially.

1. SIZE

F187-L (16"W x 34"H)

2. DIFFUSER TYPE

EAC External Prismatic Acrylic

EPC External Prismatic Polycarbonate

3. LIGHT SOURCE (Indicate wattage)

50 - 250 MH _____W

Option: pulse start ballast

35 - 250 HPS _____W

CFL Fluorescent _____W

INC Incandescent _____W

4. VOLTAGE

QT (Quad Tap 120, 208, 240, 277)

TT (Tri Tap 120, 277, 347)

NOTE: Please circle connected voltage. If none is indicated, factory will pre-wire at 120V.

120V Reactor

480 Single

5. OPTICS

BL bare lamp (standard for this fixture, due to external prismatic optics)

IES type III

IES type V

For more information on optical systems, see Options section. Photometrics are also available in IES format - consult factory or your HCI sales representative.

6. OPTIONS

FUS internal fusing

PCB luminaire integrated button type photocell

HSS house side shield

7. COLOR

Black RAL 9011

Green RAL 6005

Bronze RAL 8019

Grey RAL 7012

White RAL 9016

Custom