

F360-LED SERIES

SPECIFICATIONS



Housing

Made from heavy duty cast aluminum to withstand harsh weather.

Hardware

All exposed hardware is made of durable stainless steel, with industrial strength seals.

Interior Design & Optical

Energy efficient LED driver is mounted on a removable plate, with quick disconnect wiring to allow easy driver maintenance.

L70 at 50,000 hours with CRI≥70.

Exterior Design & Finish


Luminaire is designed to fit post top mounting or pendant mounting with our ornamental arms and poles, and is suitable for wet locations.

Finish is electrostatically applied with thermoset polyester powder-coat.

SIZES


	length	width	height	weight	tenon size	EPA
Large	19"	19"	36"	25 lbs	3"(W) x 4"(L)	2.40 ft ²
Small	-	-	-	-	-	-

PHOTOMETRICS



← polar graph

SAMPLE ILLUSTRATION
IES type III, medium



ISO footcandle →

PRODUCT	FITTER	DIFFUSER TYPE	WATTAGE	CCT	VOLTAGE	OPTICS	OPTIONS	FINIALS	COLOR
F360-L	N/A	FAC FROSTED ACRYLIC	LED	3000K	120V~277V	IES TYPE II (2)	CHY DECORATIVE CHIMNEY	N/A	STANDARD RAL 6005 GREEN 7012 GREY 8019 BRONZE 9011 BLACK 9016 WHITE *TEXTURE AVAILABLE
			35W	4000K					
			50W	5000K					
		FPC FROSTED POLYCARBONATE	55W	6000K	STEP DOWN TRANSFORMER	IV (4) V (5)	DIM DIMMING CONTROL		
			70W	± 10% VARIANCE					
			80W	480V					
		WAC WHITE ACRYLIC	90W				FUS INTERNAL FUSING		
			120W				PCB BUTTON TYPE PHOTOCELL		
			CUSTOM				HSS HOUSE SIDE SHIELD		
							TWL TWIST LOCK SYSTEM		
								CUSTOM RAL	

Product ordering sample

F360 - L - FAC - LED35W - 3000K - 120~277V - TYPE II - CHY - RAL9011 BLACK