

F361 LED Series Pendant



Description

- The F361 Series luminaire shall consist of an cast aluminum hood assembly, an aluminum cage, a multi-panel diffuser, and an internal optical system and a slip fitter (capital)
- The hinged hood, equipped with a cast aluminum finial, shall rest on the cage, which shall consist of eight diffuser panels, cast aluminum struts and a cast aluminum ring mechanically fastened together with stainless steel hardware to the gasketed fitter.
- All electrical components shall be UL listed and labeled.
- Powder coated finish

Specification

Housing

Made from heavy duty cast aluminum to withstand harsh weather.

Hardware

All exposed hardware is made of durable stainless steel, with industrial strength seals.

Interior Design & Optical

Energy efficient LED driver is mounted on a removable plate, with quick disconnect wiring to allow easy driver maintenance. L70 at 50,000 hours with CRI 70.


Exterior Design & Finish

Luminaire is designed to fit post top mounting or pendant mounting with our ornamental arms and poles, and is suitable for wet locations. Finish is electrostatically applied with thermoset polyester powder-coat.





Dimensions



Product Ordering Number

PRODUCT	LUMENS	ССТ	VOLTAGE	OPTICS	OPTIONS	FITTER	FINIALS
F361	Max 9,450 LUMENS	3000K 4000K 5000K 6000K =10% Variance	120v-277v Step down transformer 347V 480V	IES TYPE II (2) III (3) IV (4) V (5)	DIM Dimming control PCB Button type photocell HSS House side shield TWL Twist lock system	A, B C, D E, F G, H I, J K, L M, Q R, T U	FA FB FC FD FE FF FG FH FI

DIFFUSER TYPE

CAC Clear acrylic
FAC Frosted acrylic
WAC White acrylic
CPC Clear polycarbonate
WPC white polycarbonate

Color

Standard RAL 6005 Green 7012 Grey 8019 Bronze 9011 Black/Txt 9016 White Custom RAL











